

15 MAR 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



528057

(43) International Publication Date
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number
WO 2004/028190 A1

(51) International Patent Classification⁷: **H04Q 7/38,**
H04L 12/28

(21) International Application Number:
PCT/EP2003/010114

(22) International Filing Date:
11 September 2003 (11.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
TO2002A000824
20 September 2002 (20.09.2002) IT

Firenze (IT). **BARBERIS, Sergio** [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT). **MAGNANI, Nicola, Plo** [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT). **SPINI, Marco** [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT).

(74) Agents: **GIANNESI, Pier, Giovanni** et al.; Pirelli S.p.A., Viale Sarca, 222, I-20126 Milan (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **TELECOM ITALIA S.P.A.** [IT/IT]; Pizza degli Affari, 2, I-20123 Milano (IT).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **ARDUINI, Francesco** [IT/IT]; Via Castello d'Altafronte, 2, I-50122

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A METHOD FOR PROVIDING TELECOMMUNICATIONS SERVICES, RELATED SYSTEM AND INFORMATION TECHNOLOGY PRODUCT



(57) Abstract: A method for providing telecommunications services in an environment in which a plurality of telecommunications systems operate according to different standards (WLAN, UMTS) and are reachable from a terminal (T) in an integrated manner, wherein at least one of said services can be provided by more systems. Upon the provision request for the above-cited service, the method according to the invention envisages the steps of: - verifying the availability for the provision of the requested service, of at least a first (WLAN) and a second (UMTS) system, and - selecting, in an automatic and dynamic way, one between at least said first (WLAN) and said second (UMTS) system for the provision of the service being requested.

WO 2004/028190 A1



Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE,*

DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*
- *of inventorship (Rule 4.17(iv)) for US only*

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

TITLE

"A method for providing telecommunications services, related system and information technology product"

DESCRIPTION

The present invention concerns the provision of telecommunications services in an environment where at the same time two telecommunications systems working according to different standards are present.

As an example - which should however not be regarded as limiting the scope of the invention, that is fully general - the two telecommunications systems may be two mobile communication systems working according to the UMTS (Universal Mobile Telecommunications System) standard and according to a Wireless Local Area Network (WLAN) standard such as for instance the standard currently denoted as 802.11.

In the document titled "Stand-Alone Data-Cells for UMTS", presented as Tdoc FEW-0032/01 paper at the 3GPP Future Evolution Workshop held on October 18-19 2001 at Helsinki (Finland), there is described an architectural solution allowing the implementation of a full integration of both systems; such an integration is performed in the radio mode and offers the possibility of an optimum management of the network.

Closely related topics are discussed in the document "Location-based Radio Resource Management in Multi Standard Wireless Network Environments" by M.Hildebrand, G. Cristache, K.David and F. Fechter presented at the IST Mobile & Wireless Telecommunications Summit 2002, held at Thessaloniki(Greece) on June 17-19 2002. This document emphasises among other things the importance of defining solutions aimed at improving the throughput of such systems and providing the user with the best service quality.

The aim of the present invention is to provide a solution allowing the optimum exploitation of the opportunities offered by such an integration scenario. This concerns in particular the possibility of dynamically
5 performing an optimum choice of the access to the integrated system, taking into account the requirements of the network administrator (or of the operator) and of the user that is requesting a service.

According to the present invention, such an aim is
10 attained by virtue of a method having the characteristics specifically recalled in the following claims. The invention also concerns the corresponding system and the related information technology product, that may be directly loaded in the internal memory of a digital
15 computing unit and incorporates portions of software code for performing the steps of the method when the product is run on a computer.

In any case, though the solution according to the invention has been worked out with specific reference to
20 the possible application to an integration scenario such as the one previously described, it can be advantageously applied to any context wherein the same basic topics are faced. Thus the solution according to the invention is applicable to telecommunications networks working
25 according to different standards with regard to those that have been mentioned before or will be specifically mentioned, as well as to contexts wherein the integration is foreseen for a number of telecommunications systems of more than two, working together in an integrated way.

30 The solution according to the invention makes it therefore possible to provide telecommunications services in an environment wherein:

- a plurality of telecommunications systems are foreseen that work according to different standard and are

reachable from a terminal in an integrated manner,

- at least one of the services may be provided by more systems, thus according to different standards.

The solution according to the invention envisages
5 that with regard to the request of provision of the above-mentioned at least one service, there is the availability, for the provision of the service requested, of at least a first and a second system. Then, in an automatic and dynamic manner, a choice is made of one between the two
10 systems for the provision of the service requested. The selection is preferably effected through an unique module, in order to allow the selection, performed in an automatic and dynamic way, of a communication resource regarded as preferential for the provision of the service requested
15 within the integrated system.

The invention will now be described by way of a non-limiting example with reference to the appended drawings, wherein

- figure 1 depicts the general application scenario
20 of the solution according to the invention,

- figure 2 is a flow chart illustrating the implementation of a solution according to the invention, and

- figure 3 is a diagram to be used for the evaluation
25 of the load conditions of a WLAN network or a similar network in the context of the invention.

The solution according to the invention has its preferential application in a multi-mode scenario (i.e. a multi-system or multi-standard scenario) of the type
30 represented in the block diagram of Figure 1.

In principle it is foreseen that the terminals T linked to the system are multi-mode or multi-system terminals, e.g. capable of simultaneously supporting various standards, such as the UMTS and a 802.11 standard.

Such terminals are therefore capable of interfacing:

- the node, currently termed as node B, forming the element of the UTRAN (UMTS Terrestrial Radio Access Network, term indicating the network N of radio access to the UMTS system) suitable for the air transmission of the signal, without any modification with regard to the standard, and

- the Access Point, AP, i.e. the element of the 802.11 system, designed for the air transmission of the signal.

In the case of the access point AP, the information exchanged with the terminal T is essentially equivalent to the information envisaged in the AP standard mode, being however the possibility foreseen of connection to the so called Radio Network Controller (RNC), which is of standard type, but integrated with the functionalities designed for managing the 802.11 system.

In principle, the access point AP and the controller RNC must communicate with one another two parameters, namely:

- the number of users linked to the WLAN network, and

- the total bitrate of the active communications on the same WLAN network.

The parameters involved in the procedure are:

- . SIFS (Short Interframe Space) = $28\mu s$
- . backoff slot time = $50\mu s$
- . propagation delay = $1\mu s$
- . t_{slot} = $20\mu s$
- . CW min (Contention Window min) = 32
- . CW max (Contention Window max) = 256

As far as the UMTS network infrastructure is concerned, no modifications are envisaged with regard to the so called Core Network standard, in particular for the

node, called SGSN (Serving GPRS Support Node), that interfaces the UTRAN network.

All the above is set in an integration scenario wherein the nodes B and the access points AP are managed preferably by an unique controller, situated in a advanced version of the current controller RNC foreseen by the standards. Further information concerning the specific conventional modalities of implementation in Figure 1 may be derived from the document presented at the 3 GPP Future Evolutions Workshop already mentioned before and from the 3GPP specifications. The latter comprises all GSM specifications (including GPRS and EDGE) and 3G (third generation) specifications. Other terms used for the description of networks using the 3G specifications are: UTRAN, W-CDMA, UMTS (in Europe) and FOMA (in Japan).

Within the context described herein, the provision is in general envisaged of telecommunications services of different type. To define the basic concepts (though for exemplary purposes only) reference may be made to the standard classification of the services used for the UMTS standard.

In such a context the conversational service is at first dealt with: it is a type or class of service used for real time calls between users, as in the case of voice and video-conference services. The transfer time must be kept low and the time relationship between the various parts of the information flow must remain unchanged, so as to meet the characteristics of the human perception.

Then the streaming services are described for the case in which the user wishes to receive audio/video streams. It is usually a unidirectional service, provided by a server to a terminal, such as a mobile terminal. It is important that the time relations among the various parts of the information stream remain unchanged, being

however not foreseen particularly tough requirements on the information transfer times as a whole: the information is also stored at buffer level on the receiving terminal, so as to make any jitter phenomenon transparent to the human perception.

There is then the class of interactive services, that are used whenever the user requests data from a mobile apparatus, as in the case of the Internet navigation or access to a network server. In this case, important factors are the so called Round Trip Delay (RTD) and the data integrity.

There is then the class of background services, that identifies applications with a low priority execution, i.e. likely to be carried out on background. Some examples of services relating to this quality of service or QoS are the transmission of electronic mail messages or the so called SMS's. In such a case the time limits are not important, whilst the data integration is important.

The solution according to the invention aims at best exploiting the opportunities offered by the above-described context. This is made possible through a technique that dynamically carries out a optimum choice of the radio access, taking account of the requirements of the network administrator (or operator) and of the user requesting the service.

The solution described herein envisages to make a choice on the basis of the following parameters:

- class of the service requested by the user;
- availability of transmission resources (for instance, radio resources at the UMTS side as well as at the WLAN side);
- possibility of re-negotiating the service;

The solution under question works according to the following guidelines.

In principle, the UMTS standard has a 2 Mbit/s transmission capacity, whereas the 802.11b standard has a total transmission capacity equal to 11 Mbit/s. The UMTS standard is additionally capable of offering best guarantees in terms of quality of service (QoS).

The UMTS transmission resource may therefore be regarded more valuable, and that justifies the criterion of freeing or reducing as much as possible the load of the UMTS network, in order to exploit it only for services applying tough QoS requirements and in cases in which the WLAN resource is unavailable. For the rest of it, thanks to its high bitrate the 802.11b system offers a best support for the services which do not have particularly tough requirements in terms of QoS.

In practice, the system according to the invention can be implemented in the form of a module 10 (making reference to Figure 1), integrated in the RNC controller already foreseen within the integration scenario referred to in the introduction of the present invention.

A relating method of operation is illustrated in the flow chart of figure 2.

In such a flow chart, the step denoted by 100 represents a service request made by the user through the terminal T. The latter action causes the request to the RNC controller of its establishing a so called RAB (Radio Access Bearer) with given characteristics.

The characteristics required for the choice described in the sequel essentially correspond to parameters such as: class of service requested, bit rate and possibility of re-negotiating the service.

At step 102 a check is made on whether the requested service is a service of a conversational type. Since the WLAN standard is not adequate to support conversational services, if the test result of step 102 is positive, the

system directly evolves toward the step 104, where a check is made on whether the UMTS communication resource is available. If the test result at step 104 is positive, the system further evolves toward an additional step 106, thus making it possible for the service to be offered on the UMTS system. If the UMTS resource is not available (negative test result of step 104) the system evolves toward a step 108, where a check is made on whether more data rates are required.

10 In practice, at step 108 a check is made on whether, when the service under question cannot be provided with the characteristics originally requested (for instance, bitrate) said service may be provided with modified characteristics, for instance with a lower bitrate than
15 the one originally foreseen.

If the test result at step 108 is negative, the system evolves toward a step 110, notifying the impossibility of providing the service, that is not offered.

20 If instead the step 108 test is positive (which states that it possible to start a so called "re-negotiation" of the service, offering it at a lower datarate), the system returns to step 104 through a re-negotiation step 109.

25 The check on the availability of the UMTS resource is then carried out again, by making reference not to the characteristics of the service so as originally requested, but to the service characteristics resulting from the re-negotiation, for instance with reference to a lower data
30 rate.

The final result of this method of operation is given either by the provision of the service on UMTS (step 106), possibly after executing further attempts under additionally "re-negotiated conditions (should this be

possible), or the definite non-provision of the service (step 110).

If at step 102 it has been ascertained that the requested service is not a service of conversational type, 5 the system evolves toward a step 112, where a check is made on whether the requested service is a streaming service.

A service of this kind may be provided through the WLAN resource and the UMTS resource as well, the latter 10 being however regarded (for the reasons already described before) as a more valuable resource.

For this reason, if step 112 yields a negative result, showing that the service requested is a streaming service, the system evolves first toward a step 114, where 15 a check is made on whether the WLAN resource is available.

If the test result of step 114 is negative, the system evolves toward a step denoted by 116, corresponding to the allocation and provision of the service over WLAN with the appropriate data rate.

20 If instead the test of step 114 gives a negative result (because it is found out that the WLAN resource is not available: the relating verification is effected according to criteria better explained in the sequel) the system verifies, at a subsequent step 118 the system 25 verifies whether instead the UMTS resource is available.

Once the availability of the UMTS resource has been verified (negative outcome of step 118) the system evolves toward a step 120 corresponding to the provision of the streaming service over the UMTS network.

30 Should the UMTS resource be unavailable (negative outcome of step 118) the system evolves toward a step 122 substantially similar to the step 108, already seen previously.

Step 122 corresponds to a mechanism of possible re-

negotiation of the service performed by checking whether the streaming service requested by the user can be provided with different data rates, in particular by making an attempt with a lower data rate.

5 Such an attempt, represented by step 124, is however performed preferably, instead of returning toward the UMTS resource (step 118), by verifying again (step 114) the availability of the WLAN resource, regarded as less valuable and therefore to be used preferably with regard
10 to the UMTS resource.

Also in this case, as in the case previously seen in relation to the service of conversational type, the final outcome of the procedure is either the service provision over UMTS (after one or more attempts made with lower data
15 rates - step 116) or the final notification, represented by step 126, of the impossibility of offering the service.

Substantially similar criteria (without the possibility of service re-negotiation) are adopted for the provision of services of interactive or background type.

20 In particular upon a negative outcome of step 112 (the service requested is neither of conversational nor of streaming type) the system evolves toward a further selection step 127, wherein a check is made on whether the service being requested is an interactive service.

25 In the case of a positive outcome, once again the systems verifies, at a step 128, the availability of the WLAN resource.

If such a resource is available (positive outcome of step 128), the service is allocated over WLAN with the
30 appropriate data rate (step 116).

If step 128 indicates the unavailability of the resource, the system evolves toward a step 130, where the availability of the UMTS resource is verified.

In case of positive outcome, the system evolves

toward a step 132, corresponding to the provision of the interactive service via UMTS. Should step 130 have instead a negative outcome, indicating the unavailability of the UMTS resource, the system will directly evolve toward a
5 step 134 corresponding to the non-provision of the service. This is due to the fact that for the service of interactive type it is usually unlikely to suggest the execution of re-negotiation attempts with lower data-rates.

10 The possible negative outcome of the step denoted by 127, indicating that the service requested is neither of conversational nor of streaming class, and nor of interactive class, identifies the requested service as background service.

15 Once this fact has been ascertained at a step denoted by 136, the system evolves again toward a step 138 for checking the availability of the WLAN resource.

In the case of a positive outcome, the service is allocated over the WLAN network, identified as available.
20 This occurs at the step denoted 116.

If instead step 138 gives a negative outcome indicating the unavailability of the WLAN resource, the system evolves toward a step 140, where a check is made on the availability of the UMTS resource.

25 According to criteria basically similar to those adopted at steps 130, 123, 134, described before, the outcome of step 140 leads as an alternative either to the service provision over UMTS (step 142) or to the notification of the impossibility of offering the service
30 (step 144).

In short, the operation criteria described above may be traced back to the following general flow chart.

At first a check is made of the class of the service requested.

The WLAN standard is rather unsuitable to support services of conversational type, thus this type of services is immediately routed to the UMTS network.

Once said check has been made and it has been
5 ascertained that the requested service is not of conversational type, the system verifies whether or not the WLAN resource is available, by making a kind of Admission Control.

In practice, a check is made to verify that the
10 addressing of the user over the WLAN does not excessively load the network, thus causing an unacceptable degradation of the overall system performance.

If the WLAN resource is available, the service is allocated over such radio access, and the procedure ends.

15 If the WLAN resource is not available (or the check performed at the start has given a positive result notifying the request of service of conversational type), then a check is made on the availability of the UMTS resource through a procedure of Admission Control (already
20 envisaged with the UMTS system and implemented through the RNC controller).

If the UMTS resource is available, the service is allocated over such a radio access, and the procedure ends.

25 If the UMTS resource is unavailable, then the mechanism is exploited for re-negotiating the service (only in the case of conversational services or streaming) and the attempt is repeated through the procedure with lower service requirements.

30 The procedure ends in any case after a new check of the resources. If the service could be provided with lower resources, and such resources are available, the service is provided; otherwise no service provision occurs.

In the case wherein no radio resources are available

for the conversational or streaming services, it is possible to re-negotiate the service and meet the request by supplying a lower data-rate as compared to the one initially requested.

5 The attempt with a lower data-rate (steps 109 and 124) essentially corresponds to check whether it is possible to lower the data-rate requests, by trying to control again the resource with a lower rate.

To ascertain the requested service among the various
10 classes, a check procedure is envisaged at steps 102, 112 and 127 on the basis of the definitions given before.

The service allocation over WLAN or UMTS corresponds to the fact that the relating check on the resource has given a positive outcome, and the service is provided
15 through the radio access or the 802.11b or UMTS standards.

The service is not offered when the procedures end without the possibility of providing the requested service because no radio resources are available to meet the service requirements.

20 With regard to the availability verification of the resources, in the case of the UMTS resource it is possible to perform the verification by means of the formula (commonly known as such) derived from the definition of the so called "pole capacity". In the "uplink" case, such
25 a formula is then

$$\eta = (1+f) * SNR * SAF$$

Such a formula corresponds to the definition of the η parameter, identifying the cell load, standardised with regard to the max theoretical value, For example, it is
30 possible to take into account a loaded cell, when this parameter is equal to 0,7.

By f a parameter is meant that takes account of the interference contribution caused by the cells adjacent to the cell under question.

SNR stands for the signal to noise ratio required, i.e. the ratio signal to noise necessary in order that a given service is well supported.

Eventually, the parameter denoted by SAF (Service
5 Activity Factor) indicates the average time slot during which the source is active.

The above formula makes reference to an individual customer. The total value is obtained by computing the partial value of the parameter (i.e. calculating its value
10 for each active connection) and summing up all the terms thus obtained. Said formula supplies an approximate estimation of the network load and can therefore be used to schematise the behaviour of the admission control and thereby to obtain the answer to the question about the
15 available UMTS resource.

The solution just described is a purposely simplified example of control admission technique. In general the admission control techniques are more sophisticated since they take into account for instance the load on the down-
20 link connection and the availability of spreading codes in addition to the exploitation of information derived from power measurements.

With regard to the access to the WLAN network, a particularly advantageous solution is the one which
25 describes the performance degradation of the system as the number of users increases. This makes it possible to provide a kind of admission control criterion by deriving the capacity of the 802.11 standard as a function of the number of active users. The diagram of Figure 3, obtained
30 from the processing of the parameters already mentioned before (i.e. Short Interframe Space, backoff time, propagation delay, slot time, min. and max Contention Window), represents the rate value standardised to the value of the max theoretical bit rate, equal for example

to 11 Mbit/s for the 802.11b system, as a function of the number of users.

In other terms, if the active users on the WLAN are for instance 30, said users will have at their disposal
5 (making reference to the diagram of Figure 3) a total of about 6,457 Mbit/s, which are then subdivided among all the users.

It is therefore possible to check whether the bit rate totally available is sufficient to provide the
10 service requested by all the users.

As a practical example (making jointly reference to the flow chart of Figure 2 and to the diagram of Figure 3) we consider the case of a user's request for a streaming service with a 384 kbit/s that can be met also with a 144
15 kbit/s bit rate.

Assuming that at the moment 32 users are active on the WLAN (thus the available bit rate is equal, with reference to the Figure 3 diagram, to 6,3349 Mbit/s) and the load of the UMTS cell is assumed to be close to the
20 max. value of 0,7. The system is therefore close to the maximum load condition.

The evolution through the flow chart of Figure 3 is therefore the following.

Is the service of a conversational type? No.

25 Is it a streaming service? Yes.

The question is now whether the WLAN resource is available or not.

Assume that, over the WLAN, 32 users are connected (max bit rate available $0,5759 \times 11 = 6,3349$ Mbit/s) and that
30 the load on such a network is equal to 6,000 Mbit/s. The 33-th user needs, as specified before, a 384 kbit/s streaming service which can be met also with a 144 kbit/s bit rate.

The control that has been effected is the following.

The new bit rate available is $0,5706 \times 11 = 6,2766$ Mbit/s. Adding to the load value the bitrate of the request of the new user one obtains the value $6,000 + 0,384 = 6,384$ Mbit/s, which exceeds the availability.

5 Is the WLAN resource available? No.

The UMTS cell is close to the value of max. load, therefore the request cannot be met by the UMTS either.

The UMTS resource is available? No.

A question then arises:

10 Is it possible to re-negotiate the service? Yes.

The attempt is made now with 144 kbit/s, and the control effected envisages to sum up to the load data the bit-rate of the (second) request, and this brings to the value of $6,000 + 0,144 = 6,144$, Mbit/s, so that the
15 availability is not exceeded.

We ask then again:

Is the WLAN resource available?

The question receives this time a positive answer (Yes). The service is then allocated on the WLAN network
20 with the appropriate data-rate modified, i.e. reduced as compared to the data-rate initially requested.

A similar criterion can be followed for the other WLAN systems wherein use is made of numerical values typical for them, without affecting at all the decision
25 process herein described.

Obviously, keeping unchanged the principle of the invention, the details of implementation and the forms of embodiment may be widely varied, with respect to what has been described and illustrated herein, thus without
30 leaving the scope and the spirit of the present invention.

In particular it will be appreciated that - in at least a few application cases - one or more of the sets or sub-sets mentioned in the claims that follow, actually correspond to the empty set. Further it is evident that

the characteristic "deliverable" (i.e.available) or "not deliverable" (i.e.unavailable), ascribed to a given service with a view to its possible provision through a given system, must not be meant in a absolute physical
5 sense and must be instead reasonably referred to the possibility of providing a given service under the conditions and with a quality level that are acceptable to the users.

CLAIMS

1. - A method for the provision of telecommunications services in an environment in which there are a plurality of systems working according to different standards (WLAN, 5 UMTS) and reachable from a terminal (T) in an integrated way, wherein at least one of said services can be provided by several systems of said plurality, said method being characterised in that it includes with regard to the request of provision of said at least one service, the 10 steps of :

- verifying the availability for the provision of the requested service of at least a first (WLAN) and a second (UMTS) system of said plurality, and

- selecting, in an automatic and dynamic way, at 15 least one between said first (WLAN) and said second (UMTS) system of said plurality for the provision of the requested service.

2. - The method as recited in claim 1, characterised in that it includes the steps of:

- 20 - a) selecting, among said plurality of systems, at least said first (WLAN) and a second (UMTS) system, said first system (WLAN) forming with regard to said second system (UMTS), a resource to be exploited in a preferential way; said step of selecting being able to 25 bring to the subdivision of said services into:

- a first set of services to be substantially provided through said second system (UMTS), and
- a second set of services to be provided through both said first system (WLAN) and said second 30 system(UMTS),

- b) in the case (102) of a request for provision of a service within said first set, verifying (104) the availability of said second system for providing said service of said first set as requested, supplying (106)

and not supplying (110) respectively said service of said first set through said second system (UMTS), depending on whether or not said second system is available,

- c) in the cases (112, 127, 136) of a provision request for a service of said second set,

- c1) verifying (114, 128, 138) the availability of said first system (WLAN) in order to provide said service of said second set, as requested, and providing (116) said service of said second set, as requested, through said first system (WLAN), if said first system is available.

- c2) if said first system (WLAN) is unavailable for the transmission of a said service of said second set as requested, verifying the availability of said second system (UMTS) to provide said service of said second set, as requested, and providing (120, 132, 142) and not providing (126, 134, 144) said service of said second set, as requested, depending on whether or not said second system (UMTS) is available for the provision of said service of said second set, as requested.

3. - The method as recited in claim 2, characterised in that said selecting step is carried out so as to find out, within said first set, a subset of services that could be provided in at least a condition of modified communication resources, and by the fact that in the presence (108) of a provision request for a service of said subset, it includes the step of verifying (104) the unavailability of said second system (UMTS) for the provision of said service of said subset as requested and, once said unavailability has been verified, the step of re-negotiating (109) the provision request whereby said service of said subset is again requested for the provision in a condition of modified communication

resources.

4. - The method as recited in claim 2 or claim 3, characterised in that said selecting step is carried out so as to lead, within said second set, to a respective
5 subset of services that are deliverable in at least one condition of modified communication resources, and in that, when there is (112) a provision request for a service of said respective subset, it comprises the steps of verifying (114) the unavailability of at least one
10 between said first (WLAN) and said second (UMTS) system for the provision of said service of said respective subset as requested and, after verifying said unavailability (114, 118), the step of re-negotiating (124) the provision request, whereby the provision of said
15 service of said respective subset is requested again in a condition of modified communication resources.

5. - The method as recited in claim 3 or claim 4, characterised in that said selecting step is carried out so as to be able to lead, within at least one between said
20 set and said respective subset, to services that may be provided under a plurality of conditions of modified communication resources, and in that the method includes the step of repeatedly re-negotiating (109, 124) the request for service provision under subsequently modified
25 communication resources.

6. - The method as recited in any of the previous claims 2 to 5, characterised in that said selecting step comprises the step of subdividing said services into a first set comprising services of conversational class and
30 a second set comprising services included in at least one class among the classes of streaming services, interactive services, and background services.

7. - The method as recited in claim 4 and in claim 6, characterised in that said respective subset of services

of said second set includes streaming class services.

8. - The method as recited in any of the previous claims, characterised in that the selecting step is carried out by selecting said systems in the group formed
5 by the mobile communication systems.

9. - The method as recited in claim 8, characterised in that the selecting step is carried out by selecting said systems in the group formed by the UMTS, WLAN and 802.11 systems.

10. - The method as recited in any of the previous claims, characterise in that it comprises the step of verifying the availability of said first system (WLAN) on the basis of a criterion of admission control of the users, by detecting the performance degradation of said
15 first system as the number of users increases.

11. - The method as recited in claim 10, characterised in that it comprises the steps of:

- detecting the total bit rate available to the active users on said first system (WLAN),
20 - considering said first system as unavailable for a new user when the bit rate available upon the possible admission of the new user reaches a threshold value.

12. - The method as recited in any of the previous claims, characterised in that it comprises the step of
25 detecting the availability of said second system (UMTS), by defining a load parameter (η) of said second system and by considering said second system as unavailable when said load parameter reaches a threshold value.

13. - The method as recited in claim 12,
30 characterised in that said load parameter (η) is a parameter derived on the basis of "pole capacity".

14. - A system for providing telecommunications services in an environment wherein a plurality of telecommunications systems are provided that operate

according to different standards (WLAN, UMTS) and that may be accessed from a terminal (T) in an integrated manner, in which at least one of said services is deliverable by more telecommunications systems of said plurality, the
5 system being characterised in that it incorporates a module (10) capable, when there is a provision request for said at least one service, of co-operating with said plurality of telecommunications systems with the aim of:

- verifying the availability for the provision of the
10 service requested, of at least a first (WLAN) and a second (UMTS) system of said plurality of telecommunications systems, and

- selecting, in an automatic and dynamic way, between said telecommunications systems said at least a first
15 (WLAN) and a second (UMTS) system of said plurality for the provision of the service requested.

15. - The system as recited in claim 14, characterised in that said module (10) is integrated into a controller element common to said at least a first
20 (WLAN) and a second (UMTS) system of said plurality.

16. The system as recited in claim 14 or claim 15, characterised in that said module is configured:

- a) to select, within said plurality of telecommunications systems, said at least a first (WLAN)
25 and said at least a second (UMTS) system, said first system (WLAN) forming with regard to said second system (UMTS), a resource to be exploited preferably; said selection being able to bring to the subdivision of said services into:

30 - a first set of services substantially deliverable only by means of said second system (UMTS), and

- a second set of services that are deliverable by said first system (WLAN) as well as by said second system (UMTS),

- b) in the case (102) of a request for provision of a service within said first set, to verify (104) the availability of said second system for providing said service of said first set as requested, by providing (106) or not providing (110) respectively said service of said first set through said second system (UMTS), depending on whether said second system is available or unavailable,

- c) in the case (112, 127, 136) of a provision request for a service within said second set,

10 - c1) to verify (114, 128, 138) the availability of said first system (WLAN) for providing said service of said second set as requested, and to deliver (116) said service of said second set as requested by means of said first system (WLAN) if
15 said first system is available;

 - c2) if said first system (WLAN) is unavailable to provide said service of said second set as requested, to verify the availability of said second system (UMTS) for providing said service of said
20 second set as requested, and to provide (120, 132, 142) and not provide (126, 134, 144) said service of said second set, as requested, depending on whether said second system (UMTS) is available or unavailable for the provision of said service of said second set,
25 as requested.

17. - The system as recited in claim 16, characterised in that said module (10) is configured to conduct said selecting step so as said selection can lead to the presence, within said first set, of a subset of
30 services deliverable in at least a condition of reduced communication resources, and in that, in the case (108) of a provision request of a service of said subset, said module (10) is configured to verify (104) the unavailability of said second system (UMTS) for the

provision of said service of said subset as requested, and, once said unavailability has been verified, to re-negotiate (109) the provision request, whereby said service of said subset is requested again for the
5 provision in a condition of reduced communication resources.

18. - The system as recited in claim 16 or in claim 17, characterised in that the module (10) is configured to conduct said selecting step in such a way that said
10 selection can lead, within said second set, to a respective subset of services, capable of being provided in at least a condition of reduced communication resources, and in that in the case (112) of a provision request for a service of said respective subset, said
15 module (10) is configured to verify (114) the unavailability of at least one between said first (WLAN) and second (UMTS) system for the provision of said service of said respective subset as requested and, once said unavailability (114, 118) has been verified, to re-
20 negotiate (124) the provision request whereby the provision of said service of said respective subset is requested again in a condition of reduced communication resources.

19. - The system as recited in claim 17 or in claim
25 18, characterised in that said module (10) is configured to conduct said selecting step in such a way that said selection can lead, within at least one between said set and said respective subset, to services that can be provided in a plurality of conditions of modified
30 communication resources, and in that said module (10) is configured to repeatedly re-negotiate (109, 124) the request for service provision under conditions of subsequently modified communication resources.

20. - The system as recited in any of the previous

claims 16 to 19, characterised in that said module (10) is configured in a way that said selecting step can lead to the subdivision of said services into a first set comprising services of conversational class and a second
3 set of services comprising services included in at least one class among the classes of the streaming services, interactive services, and background services.

21. - The system as recited in claim 18 and claim 20,
characterised in that said respective subset of services
10 of said second set comprises services of a streaming class.

22. - The system as recited in any of the previous claims 14 to 21, characterised in that said module (10) is configured to co-operate with mobile communication
15 systems, such as said telecommunications systems of said plurality.

23. - The system as recited in claim 22,
characterised in that said module (10) is configured to co-operate with telecommunications systems included in the
20 group formed by the UMTS, WLAN and 802.11 systems.

24. - The system as recited in claim 23,
characterised in that said module (10) is integrated into a radio network type controller or RNC controller.

25. - The system as recited in any of the previous
25 claims 14 to 24, characterised in that said module (10) is configured to verify the availability of said first system (WLAN) on the basis of a criterion of admission control of the users, by detecting the performance degradation of said first system as the number of users increases.

30 26. - The system as recited in claim 25,
characterised in that said module (10) is configured to:


- detect the total bit rate available to the users active on said first system (WLAN),
- consider said first system unavailable for a new

user when the bit rate available following the possible admission of the new user reaches a threshold value.

27. - The system as recited in any of the previous
5 claims 14 to 26, characterised in that said module (10)
is configured to detect the availability of said second
system (UMTS) by defining a load parameter (η) of said
second system and by considering said second system as
unavailable when said load parameter reaches a threshold
10 value.

28. - The system as recited in claim 27,
characterised in that said load parameter (η) is a
parameter derived on the basis of "pole capacity".

29. - A Computer Program Product that may be directly
15 loaded in the internal memory of a digital computer and
that comprises portions of software code to carry out the
method according to any of the claims 1 to 13, when said
product is run on a computer.







Fig. 2

**Fig. 3**

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 03/10114

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04Q7/38 H04L12/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04Q H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 01/050790 A (NOKIA) 12 July 2001 (2001-07-12)	1-3,6, 8-10, 14-16, 20,22,23
A	page 2, line 32 - page 10, line 8; figures	4,5,7, 11-13, 17-19, 24-29
X	WO 00/70831 A (ERICSSON) 23 November 2000 (2000-11-23)	1-3,6, 8-10, 14-16, 20,22,23
	page 12, line 10 - page 26, line 21; figures	
	----- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- 'A' document defining the general state of the art which is not considered to be of particular relevance
- 'E' earlier document but published on or after the international filing date
- 'L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- 'O' document referring to an oral disclosure, use, exhibition or other means
- 'P' document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

14 January 2004

Date of mailing of the international search report

21/01/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Geoghegan, C

INTERNATIONAL SEARCH REPORT

International Publication No

PCT/EP 03/10114

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>WO 02/054677 A (NOKIA) 11 July 2002 (2002-07-11)</p> <p>page 3, line 19 - page 13, line 34; figures</p> <p>-----</p> <p>EP 1 189 405 A (MOTOROLA) 20 March 2002 (2002-03-20)</p> <p>page 3, column 3, line 25 - page 7, column 12, line 53; figures</p> <p>-----</p>	<p>1-3, 6, 8-10, 14, 15, 29</p> <p>1-3, 8-10, 14, 15</p>

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Publication No

PCT/EP 03/10114

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0150790	A	12-07-2001	FI 992850 A	01-07-2001
			AU 2521201 A	16-07-2001
			CN 1425256 T	18-06-2003
			EP 1247407 A1	09-10-2002
			WO 0150790 A1	12-07-2001
			US 2003026211 A1	06-02-2003
WO 0070831	A	23-11-2000	US 6647265 B1	11-11-2003
			AU 4966900 A	05-12-2000
			CN 1351790 T	29-05-2002
			EP 1179246 A1	13-02-2002
			JP 2003500900 T	07-01-2003
			WO 0070831 A1	23-11-2000
			SE 9902716 A	16-01-2001
			US 6668175 B1	23-12-2003
WO 02054677	A	11-07-2002	FI 20002887 A	30-06-2002
			WO 02054677 A1	11-07-2002
			US 2002085540 A1	04-07-2002
EP 1189405	A	20-03-2002	EP 1189405 A1	20-03-2002